

Top performance. Top simplicity.



Indoor
Outdoor



The lowest bottom track on the market
Just 17 mm!



Two options available
The system can be sold in full length bars or pre-cut and manufactured



Choose your desired glazing
The system allows three widths: 8, 10 and 12 mm



Bottom weight system with high quality bearings
Up to 90 kg load supported



Excellent regulation capacity
Up to 20 mm in the top track and 5 mm in the bearings



Glass assembly in seconds!
8 and 10 mm glasses can be even assembled on site



Wide locking options
The widest variety of locks on the market



Warranty
All Claroflex products have 5 years warranty

Slide is the new multitrack frameless system by Claroflex®. This is a bottom weight system.

This system has been designed with the same aim that all Our products have: simple manufacturing and installing and maintenance free. In order to achieve this goal, Slide has the least amount of components in the market, all of them of the highest quality, which assures a reliable long-lasting performance.

Moreover, our system is the most profitable one on the market for both the manufacturer and the installer because manufacturing and installation can be accomplished in just one day.

Features

- **Glass.** Tempered or laminated. 8, 10 or 12 mm
- **The lowest bottom track on the market: 17 mm**
- **Maximum panel height:** 3100 mm
- **Maximum panel width:** 1800 mm
- **Maximum panel weight:** 90 kg
- **Minimum track number:** 3

- **Possibility of sunken installation**
- **Unlimited system width.** Easily expandable by single track extensions from the basic three tracks guide
- **High-performing drainage for water and dirt**
- **Central and side opening**
- **Colours.** All options available from anodized, lacquered (RAL chart) and wood-like

Maximum dimensions

	Glass Thickness
	12 mm
Panel width	< 1800 mm
Panel height	< 3100 mm
Maximum panel size	3000 x1000 mm

	10 mm
Panel width	< 1800 mm
Panel height	< 3000 mm
Maximum panel size	3000 x1200 mm

	8 mm
Panel width	< 1800 mm
Panel height	< 2400 mm
Maximum panel size	2400 x1800 mm

Recommended installations

	SLIDE	PIVOT		SLIDE	PIVOT
Terraces/Balconies	✓	✓✓	Restaurants	✓✓	✓
Porches	✓✓	✓✓	Space dividers	✓✓	✓✓
Installations with corners	✓	✓✓			

Manufacturing and installing

- **Very simple machining.** No specialized equipment needed
- **Installation without gluing.** Just one day for 8 and 10 mm glass systems

- **No drill holes needed in the glass**
- **Top track clearance:** 20 mm
- **Bearings adjustment:** 5 mm

